

February 10, 1984

PACER RACE CAR CLASSIFICATIONS

The following classes of cars are presently considered active for racing. Typically 1 to 3 classes may be raced on a race night which is decided by the active members usually at the beginning of the racing season.

GENERAL RULES

- 1) All cars must have a minimum track clearance of .055 inches.
- 2) All four tires must touch the track.
- 3) Tires shall not protrude beyond the body.

1/32 SCALE

RTR

- 1) Width shall not exceed 2 5/8 inches.
- 2) Stock motors can not be modified.
- 3) The crown gear and tires can be changed.
- 4) The pinion gear and bearings must remain stock.
- 5) Weight may not be added.

KELLY GIRL

- 1) Hinged or sprung chassis are allowed.
- 2) An unmodified Group 12 motor will be used. (No balancing)
- 3) Car must use an inline configuration.
- 4) Body shall have 3 numbers, one on each door and one on the roof facing the driver's door.
- 5) Drivers are required.
- 6) Maximum width is 2 ~~3/4~~ inches. *2 1/2*

CAN AM

- 1) Any motor is legal. *2 1/2*
- 2) Maximum width is 2 ~~3/4~~ inches.
- 3) Drivers are required.
- 4) Body shall have 3 numbers, one on each door and one on the hood.
- 5) Any chassis is legal.

1/25 SCALE

LATE MODEL STOCK CARS

- 1) Injection molded bodies.
- 2) Motor is large Mabuchi type 36D, unmodified.
- 3) Chassis may use springs or torsion bars. NO HINGES!
- 4) Front and rear glass is required.
- 5) Drivers are required.
- 6) Chassis must be inline type.
- 7) Body shall have 3 numbers, one on each door and one on the roof facing the drivers door.
- 8) Tires must be inside body. Wheel wells are to remain stock.